

PRODUCT DESCRIPTION

Metallic anti-slip finish, with a high content of non-volatile acrylic solids, that provides a powerful molecular tension, which when dried on floor surfaces, forms a uniform and compact film with good adhesion. It is resistant to water, detergents, heel marks, abrasion caused by heavy traffic, UV rays and yellowing. Vapor permeable, stable to heat and alkalinity, and gives a crystalline product gloss, that is superior and durable.

ADVANTAGES

- Extraordinary brilliance and durability
- Resistance to heel marks
- Anti-slip
- Industrial Strength
- Hyper bright

HOW TO USE

On a clean surface, apply a very thin layer of PE-WAX using a mop or a special sheepskin waxing applicator. Let dry for about 30 minutes to allow the complete curing of the wax. Then apply the necessary layers of PE-WAX, always leaving the same amount of time between each application. Approximately 2-5 layers should be sufficient to give very good results.

IMPORTANT: Do not allow product to freeze

USAGE RESTRICTIONS: Wood floors without protective finishes.

MIXING PROPORTIONS: Use in pure form. Do not dilute.

IMPORTANT NOTICE

PROTECT THE PRODUCT FROM FREEZING. KEEP AWAY FROM CHILDREN.

All statements, recommendations and technical information contained in this document are based on tests and information, which PurEpoxy believes to be accurate as of this date; the buyer however should test this product before use. PurEpoxy assumes no obligation or liability for results obtained from the use of this product. The product and information herein are furnished at the buyer's risk. PurEpoxy will not be liable for any direct, indirect, consequential, economic or any other damage whatsoever except to replace the product and or refund the purchase price to the purchaser.